

Ultrawave Ltd Eastgate Business Park Wentloog Avenue Cardiff, CF3 2EY United Kingdom +44 (0)29 2083 7337 www.ultrawave.co.uk sales@ultrawave.co.uk

Qi300 17Litre Ultrasonic Bath

Ultrawave's **Qi-Series** are robust and reliable, delivering outstanding cleaning performance in a wide range of industries. From precision, pharmaceutical and medical device manufacturing to heavy duty cleaning in automotive and engineering processing. **Qi-Series** Ultrasonic Cleaners are Class I Medical Devices, compliant to MDR (EU) 2017/745.

The 2mm thick stainless steel tank provides longevity and durability whilst excellent ultrasonic activity is generated via Ultrawave's *Frequency Leap* technology.

Frequency Leap technology reduces dead spots and promotes homogenous cavitational activity within the tank. This provides a more consistent scrubbing action for highly effective cleaning results.





The Qi-300 is a 17Litre ultrasonic cleaner with a menu driven, LCD control panel. This allows simple adjustment of cycle time (0 to 99mins or infinity mode), temperature (ambient to 80°C), ultrasonic power and frequency mode for precise and accurate processing.

Incorporating features such as degas mode and a fluid level sensor, the

Qi-Series is reliable and durable, giving you consistent cleaning results every time.

Specifications are subject to change for continual improvements

Reg. 2558071 GB 827 1111 60 UW-DC-112-34 Rev02





Ultrawave Ltd Eastgate Business Park Wentloog Avenue Cardiff, CF3 2EY United Kingdom +44 (0)29 2083 7337 www.ultrawave.co.uk sales@ultrawave.co.uk

1ADE IN

BRITA

Qi300

17Litre Ultrasonic Bath

Construction Case	304 Stainless Steel
Construction Tank	316 Stainless Steel
Control	Digital LCD
Overall Dimensions	350 x 380 x 395mm (WxDxH)
Tank Dimensions	305 x 275 x 200mm (WxDxH)
Internal Basket Dimensions	275 x 250 x 125mm (WxDxH)
Maximum Capacity	17 Litres
Working Capacity	14.5Litres
Ultrasonic Power	300W
Ultrasonic Power (per litre)	20W/Litre
Operating Frequency	32 – 38kHz <i>Frequency Leap</i>
Maximum Heating Capacity	Ambient - 80°C
Heater Power	750W
Timer	0 - 99 minutes or Continuous
Mains Connection	230VAC
Drain Outlet	Lockable 1/2" BSP valve*
Lid	304 Stainless Steel
Basket	304 Stainless Steel
Gross Weight (inc. lid, basket & packaging)	18.8kg
Net Weight	16.3kg
Warranty	3 Years

 * Drain is located at bottom right at the back of the machine

Reg. 2558071 GB 827 1111 60 UW-DC-112-34 Rev02